



SAKRETE CONCRETE ADHESIVE

SAKRETE Concrete Adhesive is a high performance, latex-emulsion adhesive designed for use as a bonding agent between new and existing concrete and masonry surfaces. Either brush on to existing surface or mix into fresh material.

FEATURES & BENEFITS

- Bonds concrete to concrete
- Brush on or mix in
- Increases performance

USES

Can be used for patch repairs or resurfacing on concrete bridges, parking decks, industrial floors, retaining walls or sidewalks. Also use for parge-coating foundation walls and leveling concrete floors to receive overlays. This product can be used on wood substrate, solely for use with SAKRETE Self Leveling Underlayment.

PROCEDURES

Mix and substrate temperatures should be maintained between 5 °C and 30 °C (40 °F and 86 °F) for at least 24 hours prior to and 48 hours after. Not recommended to be used in areas where in-service temperatures exceed 37 °C (100 °F).

Surface Preparation: The surface to be repaired must be structurally sound and clean, as well as free from any dirt, oil, grease, paint or other contaminants. Use either mechanical means (such as sandblasting or wire brushing) or chemical means (such as a 10% trisodium phosphate solution) to thoroughly clean the area before repair. Smooth surfaces should be roughened by mechanical means or by using a 10% muriatic acid solution.

NOTE: Acid solution must be washed off the surface thoroughly with water. Clean the area to be repaired with potable water, leaving the concrete saturated but free of standing water. Some very porous concretes may require several applications of water to ensure complete saturation.

Mixing: Use as a bond coat: Apply SAKRETE Concrete Adhesive with a paint brush or roller. Coat the entire surface evenly, leaving no puddles. Apply the prepared patching material while the bond coat is still tacky.

Mixing: Use in the repair mix: Substitute SAKRETE Concrete Adhesive in place of water when mixing SAKRETE Concrete Mix, SAKRETE Sand Mix or SAKRETE Mortar Mix. Do not dilute the SAKRETE Concrete Adhesive before adding it to the mix. To obtain the desired consistency, it may be necessary to add a slight amount of water. Add only a little at a time.

NOTE: When working with concretes containing air-entrained agents (i.e. SAKRETE PSI 6000), use only as a bond coat.

Placing: Use a trowel and force the mix well into all voids in the prepared surface. Finish trowelling should be done right away. Do not over trowel.

CURING

When used in the repair mix, prevent rapid drying. During hot weather or low humidity, cover the repair surface and protect from direct sunlight for 24 hours. For the next three (3) days, moisten the surface occasionally with a fine spray of water. Under normal conditions, repaired areas may be opened for light traffic after 24 hours and heavy traffic after 48 hours. When used as a bond coat, follow the concrete product's curing recommendations.

PAINTING

Concrete must be fully cured (approximately 28 days) and dry before painting. Refer to paint manufacturer directions for application instructions.

YIELD

As a bond coat, 946 mL will cover approximately 5 m² (50 ft²), depending upon surface porosity and condition. As a bond coat, 3.78 L will cover approximately 20 m² (200 ft²), depending upon surface porosity and condition.

CLEAN UP

Clean all tools and equipment with water immediately after use.

STORAGE & SHELF LIFE

Shelf life is approximately one (1) year at temperatures between 5 °C and 20 °C (41 °F and 68 °F). Do not allow to freeze.

PACKAGING

946 mL (32 oz) plastic bottle
3.78 L (1 US gallon) plastic bottle

UPC

055226252092
055226252030

SAFETY PROCEDURES

Avoid contact with eyes and skin.

FIRST AID TREATMENT: In case of contact with eyes or skin, rinse thoroughly with water. If swallowed, drink two (2) glasses of water. Call physician.

WEBSITE

For more information and other projects, visit us at www.sakretecanada.com or call us at 866-725-7383.



.....
SAKRETE CONCRETE ADHESIVE
.....

Warranty: This product is designed to meet the performance specifications outlined in this product data sheet. If the product is used in conditions for which it was not intended, or applied in a manner contrary to the written recommendations contained in the product data sheet, the product may not reach such performance specifications. The foregoing is in lieu of any other warranties, representations or conditions, expressed or implied, including, but not limited to, implied warranties or conditions of merchantable quality or fitness for particular purposes, and those arising by statute or otherwise in law or from a course of dealing or usage of trade. [REV.0006_08/21/19]

KING PACKAGED MATERIALS COMPANY
.....

Oakville Office
555 Michigan Dr.,
Oakville, ON
L6L 0G4

Montreal Office
3825 rue Alfred-Laliberté,
Boisbriand, QC
J7H 1P7

Brantford Office
541 Oak Park Rd.,
Brantford, ON
N3T 5L8

Sudbury Office
644 Simmons Rd.,
Dowling, ON
P0M 1R0