



HD PAVER PREP

(60200206 / 4 L)
(60200207 / 18.93 L)

UPDATE

December 10, 2020

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Concrete interlocking pavers, slabs and retaining walls.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Specially formulated to remove tough efflorescence
- Prepares pavers prior to sealant application
- Brightens up the colour of pavers
- Heavy duty efflorescence cleaner

DESCRIPTION

Techniseal® HD Paver Prep is specially formulated to dissolve tough efflorescence (whitish salt) and remove ground-in dirt on pavers, slabs and retaining walls made of concrete. This ultra-powerful formula works deep without discolouring or damaging the surface. HD Paver Prep brightens up the colour, cleans evenly and extends the life of sealants by enabling them to better penetrate the material.

DIRECTIONS

BEFORE YOU BEGIN

- **Do not** use on natural stone, wet-cast pavers and stamped or poured concrete.
- Wear rubber gloves and safety goggles.
- **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations
- **Never** use this product without first consulting with local authorities regarding the application of such products, waste management and run-offs.
- **Protect** people, vehicles, property, vegetation, and other surfaces not set for cleaning from product, residue, splash, fumes and wind drift.

PREPARATION

SURFACE WETTING: To reduce the penetration of HD Paver Prep into sand joints and thus make product easier to rinse, first wet the surface to saturate joints with water; then let the surface dry, and apply product.

DILUTION: Dilution must be adjusted according to the amount of dirt and efflorescence present on the pavers. In a plastic container, dilute the product in water. Always pour the product in water, not the other way around. Test the dilution in a small area first.

Recommended dilution ratio: New pavers: 1 part product in 3 to 5 parts water. Older, never sealed pavers: 1 part product in 4 to 6 parts water. Previously sealed pavers: 1 part product in 6 to 8 parts water.

Newly installed polymeric sand: Wait at least 30 days before cleaning and sealing pavers.

APPLICATION

Application Conditions:

- Surface must be dry, warm to the touch and free of debris.
- Temperature must be between 10 and 30°C.
- Use a consistent application method over entire surface.

Important: Do not apply product with a mop or a broom. **Never** let cleaning solution dry on the surface; keep it wet at all times until it is completely rinsed off. **Never** apply the product at full strength.

Clean one section of 19 m² (200 sq. ft.) at a time. On each section, starting from the bottom of the slope, cover surface with diluted solution, making sure to cover the whole section without leaving any dry spots. Next, gently scrub the surface using a street broom; **rinse immediately and thoroughly**, until all traces of foam disappear, before proceeding to another section. In cleaning each section, overlap the edges of adjoining sections to ensure that no uncleaned strips are left between them. Once all the sections have been cleaned, rinse thoroughly and let dry. If there is any efflorescence left on the surface, repeat cleaning with a weaker solution.

COVERAGE

4L of concentrated product allows the cleaning of approximately 19 m² (200 sq. ft.) / 18.93L of concentrated product clean 95 m² (1000 sq. ft). Coverage will depend on surface condition and product dilution.

STORAGE

Store in a cool and dry place, away from the sunlight and with adequate ventilation.

PACKAGING

Product code	Size	Units per box	Units per pallet
60200206 (241-534)	4 L	4	144
60200207 (241-536)	18.93 L	—	48

WARNING

CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. Do not mix with Alkali. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Handle with care. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection: Chemical splash goggles or face shield. Use chemical-resistant, impervious gloves. Wear appropriate respirator when ventilation is inadequate. **FIRST AID TREATMENT Contains:** Phosphoric acid; Nitric acid; Sulphamidic acid. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

EMERGENCY PHONE: CANUTEC (613) 996-6666

SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.

SHIPPING

Land and sea

UN3264

Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, Phosphoric acid)

Class 8

PG: II

Exemption

- 18.93 liters needs to be transported under the hazmat regulation for any carrier that is operating a company that the mean is to transport and move mail and merchandises Trucks will need placards & the driver will need a hazmat permit.
 - It is possible to carry up to 8 x 18.93 liters without being regulated under the *Gross Mass exemption.
- 3.78 liters are exempted for transport up to a total quantity of 500 kg (approx 130 x 1 gallon), according to the 500 kg special exemption
 - It is possible to carry up to 40 x 3.78 liters without being regulated under the *Gross Mass exemption.
- 500 kg Gross Mass Exemption: It is possible for the buyer or the user to transport up to 500 kg in a vehicule.

LIMITED WARRANTY

Techniseal® warrants the HD Paver Prep against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice: User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 0.4 m² (4 sq.ft.) area. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq.ft.).